

Siro 600

The perfect combination of function, flexibility and design.



The use of fresh ground coffee and the correct pressure makes sure your coffee, espresso or cappuccino is made as it should.



The unique CoEx®-brewer makes both regular coffee and real espresso through the unique and patented pressure switch.

- the versatile range -

Siro 600

freshbrew & espresso

Coffee as expected ♦ Espresso as promised

Dimensions [mm]	H	W	D
Machine	795	370	530
Base cabinet	850	370	530

Features

Standard
 CoEx®-brewer
 QVGA-display
 Vivinox stainless steel front
 MoVeC-2000 programming & ConfigCard
 3 or 5 steps variable strength selection
 Separate hot water outlet
 Electronic temperature control
 Jug facility & Key switch
 Individual product counters
 Eco-mode, 2nd-price-line & idle-mode
 Outlet indication

Optional
 Cupsensor
 Back illuminated front
 Table base for large jugs [h=50 or 120 mm]
 Lockable base cabinet with condiment tray's
 Lockable base cabinet with tray and cupdispenser
 Enlarged wastebucket for grounds in base cabinet

Specifications

Electrical supply	
- voltage	220-240 VAC
- current	10 Amp
- frequency	50-60 Hz
Water supply	15 mm BSP
Boiler	5 Liter, 2250 W
Weight	45 kg

[manufacturer recommend to use a waterfilter.]

Selections	622	623	634
Freshbrew Coffee	◆	◆	◆
Espresso	◆	◆	◆
Decaff Coffee	◇	◇	◇
Cafe Creme	◇	◆	◆
Mocca		◇	◇
Cappuccino		◆	◆
Cappuccino [freshbrew]		◇	◇
Hot Chocolate	◆	◆	◆
Cafe au Lait		◆	◆
Cafe Latte		◇	◆
Wiener Melange		◆	◆
Espresschoc	◆	◆	◆
Chococinno		◇	◇
Creamer			◆
Sugar			◆
Hot Water	◆	◆	◆
Chilled Water	◇	◇	◇
Base Cabinet	◇	◇	◇
Table	◇	◇	◇
Cup sensor	◇	◇	◇
Paymentsystems	◇	◇	◇

◆ = standard ◇ = optional ◇ = special

The MoVeC-2000 software allows programming of alternative configurations. Ask your supplier for details.

Capacities [grams]

Freshbrew Coffee	2600	1800	1800
Cacao	2500	2500	2500
Topping		2000	1000
Sugar			1500

